

Amendments to the claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

41-54. (Withdrawn)

55. (Currently Amended) A device for monitoring glucose concentration in a biological sample of a host, the device comprising:

a ~~substantially~~ continuous glucose sensor that produces a data stream indicative of a glucose concentration in a host, the data stream including ~~comprising~~ a plurality of time spaced sensor data points; and

an integrated receiver that receives the data stream from the ~~substantially~~ continuous glucose sensor, wherein the integrated receiver includes a single point glucose monitor, a processor, and a computer readable memory, wherein the ~~comprises: a single point glucose monitor is configured to receive a biological sample from the host and to measure the concentration of glucose in the sample, the measured glucose concentration including comprising a reference data point, and wherein the ; a processor; and a computer readable memory comprising: includes~~ instructions configured to cause the processor to process the data stream received from the continuous glucose sensor, ~~; instructions configured to cause the processor to determine a rate of change of the data stream received from the substantially continuous glucose analyte sensor, [[:]] and instructions configured to cause the processor to calibrate the data stream using the glucose concentration measured by the single point glucose monitor.~~

56. (Currently Amended) The device of claim 55, wherein the integrated receiver ~~reference input module~~ is configured to reject a reference data point obtained when the rate of change of the data stream is above a threshold.

57. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a data matching module configured to match a reference data point to a sensor data point to form a matched data pair, wherein the reference data point

and the sensor data point are obtained at substantially corresponding times, and wherein the rate of change of the data stream is below a threshold at the time the sensor data point is obtained.

58. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a calibration module configured to form calibration information based at least in part on at least one reference data point and at least one sensor data point, wherein the reference data point and the sensor data point are obtained at substantially corresponding times, and wherein the rate of change of the data stream is below a threshold at the time the sensor data point is obtained.

59. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a conversion function module configured to create a conversion function based at least in part on at least one sensor data point, wherein the sensor data point is obtained when the rate of change of the data stream is below a threshold, and wherein the conversion function is configured to convert the sensor data point into a calibrated data point.

60. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a sensor data transformation module configured to convert at least one sensor data point into a calibrated data point, and wherein the rate of change of the data stream at the time at which the sensor data point is obtained is below a threshold.

61. (Currently Amended) The device of claim 55, ~~further comprising: wherein the~~ integrated receiver includes a calibration module configured to form a calibration set based at least in part on at least one matched data pair, the matched data pair including ~~comprising~~ a reference data point and a sensor data point, wherein the reference data point and the sensor data point are obtained at substantially corresponding times, [[;]] and wherein the integrated receiver includes a calibration evaluation module configured to evaluate the matched pair, wherein the calibration evaluation module is configured to

prevent the matched data pair from influencing the calibration set if the rate of change of the data stream at the time the sensor data point is obtained is above a threshold.

62. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a clinical module configured to compare a first reference data point to a second reference data point to determine whether the first reference data point is clinically acceptable, wherein the second reference data point is obtained prior to obtaining the first reference data point, and wherein the first reference data point is determined to be clinically acceptable if the difference between the first reference data point and the second reference data point is below a threshold.

63. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a clinical module configured to compare a first sensor data point to a second sensor data point to determine whether the first sensor data point is clinically acceptable, wherein the second sensor data point is obtained prior to obtaining the first sensor data point, and wherein the first sensor data point is determined to be clinically acceptable if the difference between the first sensor data point and the second sensor data point is below a threshold.

64. (Currently Amended) The device of claim 55, ~~further comprising wherein the~~ integrated receiver includes a stability module configured to determine whether the sensor data is stable, and wherein the sensor data is determined to be stable if the rate of change of the data stream is below a threshold at the time the sensor data is obtained.

65. (Currently Amended) The device of claim 64, ~~wherein the analyte comprises~~ glucose, wherein the data stream comprises measurements indicative of in vivo glucose concentration, and wherein the threshold is set at a predetermined level.

66. (Currently Amended) The device of claim 64, ~~wherein the analyte comprises~~ glucose, wherein the data stream comprises measurements indicative of in vivo glucose concentration, and wherein the threshold is 0.25 mg/dL/min.

67. (Currently Amended) The device of claim 64, ~~wherein the analyte comprises glucose~~, wherein the data stream comprises measurements indicative of in vivo glucose concentration, and wherein the threshold is 0.5 mg/dL/min.

68. (Currently Amended) The device of claim 64, ~~wherein the analyte comprises glucose~~, wherein the data stream comprises measurements indicative of in vivo glucose concentration, and wherein the threshold is greater than 0.5 mg/dL.min.

69. (Currently Amended) The device of claim 55, ~~further comprising~~ wherein the integrated receiver includes an a-user interface, and wherein the user interface is configured to request additional reference data when the rate of change of the data stream is below a predetermined threshold.

70-72. (Withdrawn)

73. (Currently Amended) The device of claim 55, wherein the integrated receiver includes an ~~comprises a user~~ interface configured to display continuous glucose sensor data and single point glucose monitor data.

74-148. (Withdrawn)